

PRODUCT DATA SHEET

P2ZE-FLASH

LIQUID APPLIED FLASHING & JOINT SEALING COATING



PATH 2 ZERO ENERGY

DESCRIPTION

P2ZE-Flash is a single component silyl terminated polymer sealant intended for use as a liquid-applied flashing and joint sealing product. It is solvent free, isocyanate free, and bonds to most common building materials without priming. It forms a seamless flexible barrier that prevents penetration of unwanted water and air through the building envelope while being breathable to allow damp surfaces to dry. It may be exposed to UV light and weather for up to 12 months.

ADHESION

P2ZE-FLASH adheres well to a wide variety of substrates, generally with no primer required. It can bond to damp substrates and cure in wet weather. ASTM C794

APPLICATION

The recommended application thickness is 20-35 wet mils. At this thickness, the estimated coverage is 10 sf per 20 fl. oz. Surfaces must be clean and free of contaminants. It is recommended to test substrate compatibility with PZZE-FLASH prior to full application. Curing/drying speed will be influenced by temperature and humidity conditions.

CLEAN UP

Clean tools and equipment with mineral spirits or similar solvent right after use. Tool out any excess from gun tip and use material. Next day clean out cured P2ZE-FLASH in tip to reuse. Best advice on clothes is to not even try but dedicate them to liquid flashing days.

STORAGE AND HANDLING

Store in a cool, dry place. Keep container tightly closed when not using. Do not open container until preparation work has been completed. Do not alter or mix with other chemicals. When stored at or below 80°F (27°C) P2ZE-FLASH has a shelf life of 12 months after the date of manufacture. Dispose of unused product and container in accordance with local, state and federal regulations.

ADVANTAGES

- •AAMA compliant for use as perimeter sealing compound
- •Silyl Terminated Polymer provides superior long term adhesion, crack filling and weathering characteristics
- •Fire Rated
- •Bonds to most common building material without priming, including green concrete
- •Single component saves time no mixing
- •Bonds and cures in wet weather and on damp substrates
- •Can handle rain immediately after application
- •May be exposed to UV and weather for up to 12 months
- •Compatible with most sealants and waterproofing or air barrier components
- •Solvent free. Isocyanate free. Ortho-Phthalate Free.
- •No shrinkage. No staining. No yellowing.
- •Breathable allows damp surfaces to dry
- •Will not support mold growth
- Passes ASTM E84 Standard test method for surface burning characteristics of building materials
- •Low VOC
- •May be painted

PHYSICAL PROPERTIES

Description	Criteria	Results
Composition		Silyl Modified Polymer
Application Temperature		≥ 40°F (4.4°C)
Hardness, Shore A	ASTM C661	27
Tensile Strength	ASTM D412	> 180 psi
Elongation at Break	ASTM D412	1,400%
Water Vapor Transmission	ASTM E96	13.6 perms
Adhesive Strength to Substrates	ASTM C794 ≥5 pli	Pass
Water Penetration Around Nails	ASTM D1970 Shall pass 31 mm (1.2 in) of water	Pass
Accelerated UV Aging	ASTM G254, ASTM C794 ≥5 pli	Pass
Elevated Tempera- ture	AAMA 711, ASTM C794 ≥5 pli	Pass
Thermal Cycling	AAMA 711, ASTM C794) ≥5 pli	Pass
Crack Bridging	ASTM C1305) Water holdout of 550mm for 24hr with 1/16" crack	Pass

TO THE MAXIMUM EXTENT ALLOWED BY LAW, PASSIVE HOUSE PROVISIONS LLC DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT

LEGAL DISCLAIMER

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, agreement, or substitute for expert or professional advice. Passivehouse Provisions LLC. expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any other process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. The user is responsible for testing the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. PASSIVE HOUSE PROVISIONS, LLC DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem and must be submitted with written proof of purchase. Under this warranty, we will provide, at no charge, replacement materials for, or refund the purchase price of any product proven to be defective when used in strict accordance with our published recommendations and in applications considered by us as suitable for this product. The determination of eligibility for this warranty, or the choice of the remedy available under this warranty, shall be made in our sole discretion and any decision made by PASSIVE HOUSE PROVISIONS LLC shall be final. This warranty is in lieu of any and all other warranties, expressed or implied, including but not limited to, a warranty of merchantability or fitness for a particular purpose and in no case will PASSIVE HOUSE PROVISIONS LLC be liable for damages other than those expressly stated in this warranty, including but not limited to, incidental or consequential damages.



Passivehouse Provisions LLC Path 2 Zero Energy Coatings 302-589-4172